



# CMM-40

## INDUSTRIAL MULTIMETER



### Standard accessories:

- test leads (2 pcs.)
- battery 9V
- K type temperature probe

**WAPRZCMP1**

**WASONTEMK**

- carrying case
- waterproof plugs (2 pcs.)
- operating manual



# CMM-40

Industrial multimeter CMM-40 has been designed for the purpose of measurements of AC/DC voltage, AC/DC current, resistance, capacitance, frequency (electrical and electronic), duty cycle, temperature and also for testing diodes and continuity.

**The most important features of CMM-40 are:**

- Autoranging/manual range selection.
- „DATA HOLD” function, for holding measured values.
- „REL” function, which allows you to make measurements relative to a stored reference value.
- „MAX/MIN” function.
- „PEAK HOLD” function.
- Memory for 2000 measurement results.
- Continuity test with acoustic signalling (beeper).
- „AUTO-OFF” function.
- Display 4½ digits (40000 max).
- Double molded, waterproof enclosure.

## Frequency measurement (electronic)

Range	Resolution	Accuracy
40,000 Hz	0,001 Hz	±(0,1% m.v. + 1 digit)
400,00 Hz	0,01 Hz	
4,0000 kHz	0,0001 kHz	
40,000 kHz	0,001 kHz	
400,00 kHz	0,01 kHz	
4,0000 MHz	0,0001 MHz	
40,000 MHz	0,001 MHz	
100,00 MHz	0,01 MHz	not specified

- Sensitivity: 0,8V rms min. @ 20% to 80% duty cycle and <100kHz; 5V rms min @ 20% to 80% duty cycle and > 100kHz

## Frequency measurement (electrical)

Range	Resolution	Accuracy
40,00 Hz...10,000 kHz	0,01 Hz...0,001 kHz	± 0,5% m.v.

- sensitivity: 1V rms

## Duty cycle measurement

Range	Resolution	Accuracy
0,10...99,9%	0,01%	±(1,2% m.v. + 2 digits)

- pulse width: 100µs - 100ms,
- frequency width: 5Hz...150kHz.

## Temperature measurement

Range	Resolution	Accuracy *
-50,0°C...+1200,0°C	0,1°C	±(1% m.v. + 2,5°C, 4,5°F)
-58,0°F...+2192,0°F	0,1°F	

\*) probe (K type) accuracy not included

## Other technical data:

- power supply
  - diode test
  - continuity test
  - over range indication
  - crest factor
  - PEAK
  - sampling rate
  - input impedance
  - display
  - store capacitance
  - dimensions
  - weight
  - fuses
  - auto power OFF
  - accordance with following standards
  - quality standard
- 9V battery type 6LR61  
I=0,9mA, U<sub>o</sub>=2,8V DC  
I<0,35mA, sound signal for R<35Ω  
OL displayed  
≤ 3 at full scale up to 500V,  
decreasing linearly to ≤ 1,5 at 1000V  
captures peaks >1ms  
2 times per second  
10MQ (V DC), 9MQ (V AC)  
40000 counts backlit LCD with bargraph, 4½ digits  
2000  
187 x 81 x 55 mm  
342 g  
mA, µA range: 0,5A/1000V ceramic fast blow  
A range: 10A/1000V ceramic fast blow  
15 min.  
EN 61010-1:2004  
EN 61010-2-032  
ISO 9001

I<0,35mA, sound signal for R<35Ω  
OL displayed  
≤ 3 at full scale up to 500V,  
decreasing linearly to ≤ 1,5 at 1000V  
captures peaks >1ms  
2 times per second  
10MQ (V DC), 9MQ (V AC)

40000 counts backlit LCD with bargraph, 4½ digits

2000

187 x 81 x 55 mm

342 g

mA, µA range: 0,5A/1000V ceramic fast blow

A range: 10A/1000V ceramic fast blow

15 min.

EN 61010-1:2004

EN 61010-2-032

ISO 9001

## DC voltage measurement

Range	Resolution	Accuracy
400,00 mV	0,01 mV	±(0,06% m.v. + 4 digits)
4,0000 V	0,0001 V	
40,000 V	0,001 V	
400,00 V	0,01 V	
1000,0 V	0,1 V	±(0,1% m.v. + 5 digits)

## AC voltage measurement (True RMS)

Range	Resolution	Accuracy
400,00 mV	0,01 mV	±(1% m.v. + 40 digits)
4,0000 V	0,0001 V	
40,000 V	0,001 V	
400,00 V	0,01 V	
1000,0 V	0,1 V	±(1% m.v. + 30 digits)

• frequency range: 50...1000Hz.

## AC/DC current measurement (True RMS)

Range	Resolution	Accuracy
400,00 µA	0,01 µA	dla DC ±(1,0% m.v. + 3 digits)
4 000,0 µA	0,1 µA	
40,000 mA	0,001 mA	
400,00 mA	0,01 mA	
10,000 A	0,001 A	dla AC ±(1,5% m.v. + 30 digits)

• 20A: 30 sec max with reduced accuracy.

## Resistance measurement

Range	Resolution	Accuracy
400,00 Ω	0,01 Ω	±(0,3% m.v. + 9 digits)
4,0000 kΩ	0,0001 kΩ	
40,000 kΩ	0,001 kΩ	
400,00 kΩ	0,01 kΩ	
4,0000 MΩ	0,0001 MΩ	±(0,3% m.v. + 4 digits)
40,000 MΩ	0,001 MΩ	
40,000 MΩ	0,001 MΩ	±(2,0% m.v. + 10 digits)

## Capacitance measurement

Range	Resolution	Accuracy
40,000 nF	0,001 nF	±(5,0% m.v. + 7 digits)
400,00 nF	0,01 nF	
4,0000 µF	0,0001 µF	
40,000 µF	0,001 µF	
400,00 µF	0,01 µF	±(3,0% m.v. + 5 digits)
40,000 mF	0,1 µF	
40,000 mF	0,001 mF	±(5,0% m.v. + 5 digits)

„m.v.” - measured value

## Electric security:

- type of insulation
  - measurement category
  - protection class acc. to EN 60529
- double, according to EN 61010-1 and IEC 61557  
CAT III 1000V acc. to EN 61010-1:2004  
IP67

## Rated operational conditions:

- operating temperature
  - storage temperature
  - operating humidity
  - operating altitude
- 0...+40°C  
-20...+60°C  
max 80% up to 87°F (31°C)  
decreasing linearly to 50% at 104°F (40°C)  
max 2000m